Reg. No. :

Question Paper Code: 71468

B.E./B.Tech. DEGREE EXAMINATION, APRIL/MAY 2015.

Seventh Semester

Electronics and Communication Engineering

EC 2402/EC 72/10144 EC 702 — OPTICAL COMMUNICATION AND NETWORKING

(Regulation 2008/2010)

(Common to PTEC 2402 – Optical Communication and Networking for B.E. (Part-Time) Sixth Semester – Electronics and Communication Engineering (Regulation 2009))

Time : Three hours

5

Maximum : 100 marks

Missing data may be suitably assumed.

Answer ALL questions.

PART A — $(10 \times 2 = 20 \text{ marks})$

- 1. Calculate the critical angle of incidence between two substances with different refractive indices, where $n_1 = 1.5$ and $n_2 = 1.46$.
- 2. State Snell's law.
- 3. Define signal attenuation.
- 4. What are bending losses? Name any two types.
- 5. Define power-bandwidth product.
- 6. Contrast the advantages of PIN diode with APD diode.
- 7. Define bit-error rate.
- 8. List any two advantages of trans-impedance amplifiers
- 9. What is SONET?
- 10. What is Soliton?

PART B — $(5 \times 16 = 80 \text{ marks})$

- 11. (a) (i) For a multi-mode step-index fiber with glass core($n_1=1.5$) and a fused quartz cladding ($n_2=1.46$), determine the acceptance angle (θ_{in}) and numerical aperture. The source to fiber medium is air. (6)
 - (ii) Explain the ray propagation into and down an optical fiber cable. Also derive the expression for acceptance angle. (10)

Or

- (b) (i) Describe a step index and graded index cable. (6)
 - (ii) Contrast the advantages and disadvantages of step-index, gradedindex, single-mode propagation and multi-mode propagation. (10)
- 12. (a) What are the loss or signal attenuation mechanisms in a fiber? Explain.

Or

- (b) (i) Discuss in detail about fiber splicing.
 - (ii) What are the primary requirements of a good fiber connector design? (6)
- 13. (a) (i) With neat sketch, explain the working of a light emitting diode. (8)
 - (ii) Derive an expression for the quantum efficiency of a double hetro-structure LED. (8)

Or

- (b) (i) A photodiode is constructed of GaAs which has a band gap energy of 1.43 eV at 300K. Find the long wavelength cut-off. (4)
 - (ii) Derive an expression for the mean square photo detector noise current.
 (8)
 - (iii) Write a note on response time. (4)
- 14. (a) With schematic diagram, explain the blocks and their functions of an optical receiver.

Or

- (b) (i) A digital fiber optic link operating at 850 nm requires a maximum BER of 10⁻⁹. Find the quantum limit in terms of the quantum efficiency of the detector and the energy of the incident photon. (6)
 - (ii) Explain the attenuation and dispersion measurements in detail. (10)
- 15. (a) (i) Explain the principle of WDM networks. (8)
 - (ii) Discuss the non linear effects on optical network performance. (8)

Or

- (b) (i) Explain the features of Ultra High capacity networks. (8)
 - (ii) Explain OTDR and its applications.

(8)

(10)